

EPOXGROUT® DATA SHEET

Product

Epoxy Grout 3Kg Resin + 1 Kg Hardener, resistant to chemicals, high resistance and easy to apply and clean.

Composition

2 part epoxy sealer composed by a resin and a hardener.

Features and applications

- Allow 12 hours before stepping in. Can hold mechanical loads 24 hours after setting.
- When cured it will resist salty water, acids, organic liquids, mineral compounds, etc.
- Solid colour. Easy to clean. High resistance.
- Good penetration in joints up to 15 mm.
- Swimming pools, chemical or food industries, laboratories, hospitals, public showers, industrial kitchens, etc.

Substrates

- Empty joints must be dry and clean in all their length and depth.
- Wait 24 hours after wall application and 48 hours after floor application.

Instructions for use

- Mix energetically both components (best with a drill mixer) until a uniform and homogeneous paste is obtained.
- Do not mix partially.
- Use a spatula or a rubber trowel to grout and to press the material. Application should be diagonally to the joints.
- Remaining material must be discarded within 75 min with a hard sponge and water. Then a soft sponge can be used.
- Any light remains on the tiles should also be cleaned out.

USE AS AN ADHESIVE

- Also suitable to fix glass/porcelain mosaic on walls and floors as well as for ceramic tiles on floors.
- Complies with EN 12004 standards when used as an adhesive.

Packaging

4- kilo plastic gallons (3+1Kg).