

MORTAR MIX® DATA SHEET

Dry mortar

For plastering and masonry jobs in general.

Product based on high resistance cement, selected aggregates, and other additives

Features and applications

- To be applied directly on brickworks.
- Masonry works.
- Plaster and stucco works.
- Terrazzo floorings.

Substrates

- Conventional cement and brickwork based substrates.
- Substrates must be resistant, stable, sound and clean, free of dust, de-molding agents, organic products, etc.
- In case of hot or windy weather conditions or when applying over absorbent substrates, it is advisable to wet the substrate and wait till the thin layer of water disappears.
- Do not apply on clay or on paint.

Instructions for use

- Add water and mix by hand or mechanically until it takes on an even and workable consistency.
- For plaster works, spread the mortar on the substrate with a trowel and let rest enough time before floating.

Cautions and recommendations

- Do not apply below 5°C nor above 40°C.
- Do not apply when there is a risk of frost, rain, strong wind or direct sunlight.
- For a thickness of over 1,5 cm, it is advisable to apply the product in two coats.
- In extreme weather conditions (strong winds or high temperatures) it is necessary to water the product with light sprinklers the day after applying it.

Technical data

(Statistical data obtained under standard conditions)

Aspect	GREY powder
Density of mixed product	2,0 +/- 0,2 g/cm ³
Adhesion	> 0,2 N/mm ²
UNE-EN 998-1 Classification	GP CSIV W0
Approximate yield	Depending on use

Packaging

25 kg plastic-lined paper bags

Shelf life: 1 year in sealed original packaging, sheltered from weather conditions and humidity.

Note

Instructions of use are given based on our testing and knowledge and do not imply any commitment. Said instructions do not free the user from examining and verifying the product for its correct use.