

PlasterFix

Plaster Fix, a single-layer gypsum plaster for manual application used for the interior of coating walls and ceilings and also for creating architectural designs with smooth surfaces.

Composition

Plaster Fix is of high purity gypsum and dolomite from Spain, it gives both ease of workability and hardness with European Quality Standards.

Features and Applications

Plaster Fix can be used to repair substrates before applying Plaster Fix Plus mechanically.

This material has a high coefficient of thermal conductivity and given its porous structure provides good sound insulation.

It is also a natural regulator of humidity and moisture providing optimum comfort in the interior of the house, residence, commercial office, etc.

It is both fire protection and abrasion resistant.

Plaster Fix is fast drying with up to 35 minutes open time.

Special advantages of using Plaster Fix:

- It is light in weight and more durable.
- It has low thermal conductivity.
- It is very good fire resistant and hence a very good insulating material.
- It does not shrink while setting. Therefore, it does not develop cracks on heating or setting.
- It forms a thick surface to resist normal knocks after drying.
- It mixes up easily with water and is easy to spread and level.
- It has good adhesion on fibrous materials.
- It gives a firm surface on which the colours can settle.
- It has no appreciable chemical action on paint and does not cause alkali attack.
- Plaster Fix gives a decorative interior finish. Its gypsum content provides a lot of shine and smoothness.
- It can easily be moulded into any shape.