

Stamp-Fix® DATA SHEET

A high-performance monochrome mortar suitable to repair existing **Perma-Stamp®** floors (Stamped Concrete Floors).

Features and Applications

- High adhesion and anti-slip properties.
- **Stamp-fix®** (10kgs) requires 5 liters of water for mixing.
- With a suitable roller, apply the mixed product on the surface of the prepared floor and avoid the in-between lines of the decorative concrete.
- The same bucket could be used for the mixing process.
- The cover area after mixing is 40 m² per coat.
- Available in 10 basic colors: SILVER, BORDEUX, CHROME, CLAY, TERRACOTA, CUERO, ALBERO, IVORY, WALNUT AND PIZARRA

Silver	Bordeux	Chrome	Clay	Terracota	Cuero	Albero	Ivory	Walnut	Pizarra
									

Instructions for Use

- The old floor and surface must be clean, dry and free of greasy materials.
- Existing cracks should be repaired with **Perma-Stamp Plus®**.
- Only after the repair work has dried you can apply the **Stamp-Fix®**.
- First, pour 2.5 liters of water into the **Stamp-Fix®** 10 kgs bucket and mix well, using either a mechanical mixer or manually until you have a homogeneous mix. Add the remaining 2.5 liters of water and mix again. The product is now ready for use.
- Apply two coats for a better sealing of the surface.
- Finish the flooring by applying **PERMAFIX® Varnish**.

Note

- Do not apply above 30°C.
- Do not apply when there is a risk of rain or strong wind.

Packaging

10 Kg Bucket Container.

Expiration

1 year in original packaging, sheltered from weather conditions and humidity.