

CEMENT WATERPROOF 1 KG.

Description

Permafix Waterproof Admixture allows you to transform highly porous mortar into a water-resistant, crack resistant barrier that withstands elements. It is suitable for use in tropical and hot climatic conditions. Building maintenance and repair costs can be significantly decreased by improving durability and by preserving the original appearance. used to waterproof cement/sand mortars, screeds and renders for walls, facades, floor toppings and jointing mortars.

Advantages

Permafix Waterproof Admix contains pore sealing and water-repelling substances which enhances the water resistance of your mortar.

Product Data

Type Blend of organic and inorganic chemicals

Colour Off-White Powder

Packaging 1 kg bags, 10 bags per carton

Storage Condition Store in a dry area in original packaging between 5C and 35C. Protect from direct sunlight

Shelf life 12 months minimum if stored properly in original unopened packaging

Density Approximately 0.9 kg/lit.

Application Details

Dosage 2% by weight of cement.

Dispensing Permafix Waterproof Admix is added to the dry mixed cement/sand prior to the addition of water.

Concrete Placing The standard rules of good concreting practice (production as well as placing) must also be observed when using mixed mortars and concrete.

Cleaning Clean all equipment and tools with water immediately after use.

Notes

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.value of the used goods.